

# ACOUSTIC PLASTER

16 mm thick Eco-friendly fire resistant acoustical material, Soundproof Cellulose acoustic Spray a cellulosic acoustic insulation, sprayed using proprietary adhesive with a sound absorption of NRC 0.8, or higher as per ASTM C423 made of fire resistive material that achieves a flame spread rating of BS 1, do when tested in accordance with BS 476.with thermal conductivity W/mK 0.037 as per TS ISO 8302:2002-4. Material should have achieved class BA: 0 for Bacteria & Fungal test as per TS EN 15101-1:2013 Annex F. The material to be supplied and installed on fully cured concrete/gypsum/Lath/metal on ceiling/wall surface at site using necessary supports and scaffolding and to be installed by skilled labour as per manufacturer's application guidelines. The plaster should be finished as per shade specified by the architect



## ACOUSTIC PLASTER

16 mm thick Eco-friendly fire resistant acoustical material, Soundproof Cellulose acoustic Spray a cellulosic acoustic insulation, sprayed using proprietary adhesive with a sound absorption of NRC 0.8, or higher as per ASTM C423 made of fire resistive material that achieves a flame spread rating of BS 1, do when tested in accordance with BS 476. with thermal conductivity W/mK 0.037 as per TS ISO 8302:2002-4. Material should have achieved class BA: 0 for Bacteria & Fungal test as per TS EN 15101-1:2013 Annex F. The material to be supplied and installed on fully cured concrete/gypsum/Lath/metal on ceiling/wall surface at site using necessary supports and scaffolding and to be installed by skilled labour as per manufacturer's application guidelines. The plaster should be finished as per shade specified by the architect.

S.NO	DESCRIPTION	SPECIFICATION
1	CORE	CELLULOSE FIBER
2	SIZE	CUSTOMIZED
3	THICKNESS	10 - 75MM
4	NRC	0.50 - 0.92
5	THERMAL CONDUCTIVITY	0.037 W/MK
6	COLOR	WHITE & GREY
7	FIRE RESISTANCE	BS476

In case of any further queries, please do reach out us at [care@anakan.in](mailto:care@anakan.in)

Thanking you,  
For ANAKON INDIA

This is an electronically generated document, hence does not require a signature.



## ANAKON INDIA

CEILING | ACOUSTICS | SOUND BARRIER | TERRACOTTA

CORRESPONDENCE ADDRESS: - OFFICE 411, 4<sup>TH</sup> FLOOR ANSAL CHAMBER 11, 6 BHIKAJI CAMA PLACE NEW DELHI-110066  
ADDRESS: - 189-A/1, PLOT NO. 31 KHASRA NO. 73, SAVITRI NAGAR, PO MALIVIYA NAGAR NEW DELHI - 110017

PHONE NUMBER: 18003132100 | EMAIL: [info@anakan.in](mailto:info@anakan.in)