

Acoustical Perforated Tiles

Wooden Acoustical Suspended Ceiling Panels are high performance acoustic products with an exceptional visual appearance.

Acoustic wood tiles come in a variety of configurations to meet all internal and acoustic requirements, providing sound reflection and absorption through grooves and vents. Acoustic insulation pads can be used to increase NRC values. Acoustical

Suspended Ceiling System – Tegular edge tile Lay in on 24 mm exposed Grid. The high Grade MDF panels having melamine laminated faced with hole or Slot system backed with a nonwoven fabric covering of 0.2mm for providing sound absorption via acoustic impedance method. The tiles should have Humidity Resistance (RH) of 99%, NRC 0.75, Light Reflectance >84% with Fire Resistance as per BS476 (Part 6 & 7) in module size of 595 X 595 X 12 mm@ 400kg/m³ density. The Grid should be 24 mm wide T sections i.e. the Main Runner 3000mm in web height of 32 mm, 1200 mm & 600 mm Cross Tees in web height of 26mm to comprise main runner spaced at 1200mm centers securely fixed to the structural soffit using suspension system at 1200mm maximum centre. The First/Last suspension system at the end of each main runner should not be greater than 450mm from the adjacent wall. Flush fitting 1200mm long cross tees to be interlocked between main runners at 600mm centre to form 1200 x 600 mm module. Cut cross tees longer than 600mm require independent support. 600 x 600mm module to be formed by fitting 600mm long flush fitting cross tees centrally between the 1200 mm cross tees. Perimeter trim to be wall angles of size 3000x19x19mm, secured to walls at 450 mm maximum centers and as per the drawing and the work complete in all respects to the satisfaction of Engineer in-charge.



T GRID 24 MM

S.NO	DESCRIPTION	MAIN- TEE
1	MATERIAL	GALVANIZED IRON
2	TYPE OF SHEET	PRE-COATED
3	WEB HEIGHT	38MM (+-0.5mm)
4	FLANGE	24MM(+/-0.5mm)
5	THICKNESS	0.33MM(+/-0.05mm)
6	LENGTH	3600MM(+/-0.5mm)
7	COLOUR	WHITE
8	GALVANIZING COATING	120GSM

S.NO	DESCRIPTION	CROSS- TEE(4FT)
1	MATERIAL	GALVANIZED IRON
2	TYPE OF SHEET	PRE-COATED
3	WEB HEIGHT	28MM(+0.5mm)
4	FLANGE	24MM(+/-0.5mm)
5	THICKNESS	0.33MM(+/-0.05mm)
6	LENGTH	1200MM(+/-0.5mm)
7	COLOUR	WHITE
8	GALVANIZING COATING	120GSM

S.NO	DESCRIPTION	CROSS- TEE(2FT)
1	MATERIAL	GALVANIZED IRON
2	TYPE OF SHEET	PRE-COATED
3	WEB HEIGHT	28MM(+0.5mm)
4	FLANGE	24MM(+/-0.5mm)
5	THICKNESS	0.33MM(+/-0.05mm)
6	LENGTH	600MM(+/-0.5mm)
7	COLOUR	WHITE
8	GALVANIZING COATING	120GSM

S.NO	DESCRIPTION	WALL ANGLE
1	MATERIAL	GALVANIZED IRON
2	TYPE OF SHEET	PRE-COATED
3	WEB HEIGHT	24MM(+0.5mm)
4	FLANGE	24MM(+/-0.5mm)
5	THICKNESS	0.40MM(+/-0.05mm)
6	LENGTH	3600MM(+/-0.5mm)
7	COLOUR	WHITE
8	GALVANIZING COATING	120GSM

In case of any further queries, please do reach out us at care@anakon.in

Thanking you,
For ANAKON INDIA

This is an electronically generated document, hence does not require a signature.



ANAKON INDIA

CEILINGS | ACOUSTICS | SOUND BARRIER | TERRACOTTA

CORRESPONDENCE ADDRESS: - OFFICE 411, 4TH FLOOR ANSAL CHAMBER 11, 6 BHIJKI CAMA PLACE NEW DELHI-110066

ADDRESS: - 189-A/1, PLOT NO. 31 KHASRA NO. 73, SAVITRI NAGAR, PO MALIVIYA NAGAR NEW DELHI - 110017

PHONE NUMBER: 18003132100 | EMAIL: info@anakon.in

TECHNICAL DATA SHEET

WOODEN ACOUSTIC CEILING

Wooden Acoustical Suspended Ceiling Panels are high performance acoustic products with an exceptional visual appearance. Acoustic wood tiles come in a variety of configurations to meet all internal and acoustic requirements, providing sound reflection and absorption through grooves and vents. Acoustic insulation pads can be used to increase NRC values. Acoustical Suspended Ceiling System - Tegular edge tile Lay in on 24 mm exposed Grid. The high Grade MDF panels having melamine laminated faced with hole or Slot system backed with a nonwoven fabric covering of 0.2mm for providing sound absorption via acoustic impedance method. The tiles should have Humidity Resistance (RH) of 99%, NRC 0.75, Light Reflectance >84% with Fire Resistance as per BS476 (Part 6 & 7) in module size of 595 X 595 X 12 mm@ 400kg/m³ density. The Grid should be 24 mm wide T sections i.e. the Main Runner 3000mm in web height of 32 mm, 1200 mm & 600 mm Cross Tees in web height of 26mm to comprise main runner spaced at 1200mm centers securely fixed to the structural soffit using suspension system at 1200mm maximum centre. The First/Last suspension system at the end of each main runner should not be greater than 450mm from the adjacent wall. Flush fitting 1200mm long cross tees to be interlocked between main runners at 600mm centre to form 1200 x 600 mm module. Cut cross tees longer than 600mm require independent support. 600 x 600mm module to be formed by fitting 600mm long flush fitting cross tees centrally between the 1200 mm cross tees. Perimeter trim to be wall angles of size 3000x19x19mm, secured to walls at 450 mm maximum centers and as per the drawing and the work complete in all respects to the satisfaction of Engineer in-charge

S.NO	DESCRIPTION	DETAILS
1	SIZE	595X595X12MM
2	CORE	HDHMR FIBER BOARD/MDF
3	DENSITY	400 KG/M ³
4	FIRE RESISTANCE	BS 476 (PART 6 & 7)
5	NRC	0.75
6	HUMIDITY RESISTANCE	99%
7	LIGHT REFLECTANCE	>84%

In case of any further queries, please do reach out us at care@anakon.in

Thanking you,
For ANAKON INDIA

This is an electronically generated document, hence does not require a signature.



ANAKON INDIA

CEILING | ACOUSTICS | SOUND BARRIER | TERRACOTTA

CORRESPONDENCE ADDRESS: - OFFICE 411, 4TH FLOOR ANSAL CHAMBER 11, 6 BHICAJI CAMA PLACE NEW DELHI-110066
ADDRESS: - 189-A/1, PLOT NO. 31 KHASRA NO. 73, SAVITRI NAGAR, PO MALIVIYA NAGAR NEW DELHI - 110017
PHONE NUMBER: 18003132100 | EMAIL: info@anakon.in